

News Bulletin

New Product Release



6/27/13

PRODUCT NAME: Akrofoam™ 2000 Nozzle

AKRON PART NUMBER: Style 4478

PRODUCT DESCRIPTION

The Akrofoam 2000 is a self-educing master stream nozzle designed for foam flow rates up to 2000 gpm (7600 lpm). This is the perfect combination of a nozzle and eductor all-in-one. The Akrofoam nozzle provides superior stream performance with outstanding reach. Using a manual pattern control, the nozzle can go from a straight stream to wide fog pattern in seconds. This new nozzle also features a foam orifice plate storage cup, located directly on the nozzle, ensuring that you have access to the correct metering plates for quick adjustments to foam flow rates.



For rapid on the go changes in foam flow proportioning rates, an optional foam metering/shutoff valve is available with settings of 1%, 3%, and 6% at the 750 and 1000 gpm flows or 1% and 3% at the 1500 and 2000 gpm flows.

FEATURES

- All-in-one nozzle with built-in eductor
- User adjustable from straight stream to wide fog pattern
- Spring loaded baffle quickly changes your flow setting with a simple push and turn of the baffle head
- Made from durable, lightweight, Pyrolite® material

PRODUCT DETAILS

- Flow rate: 750, 1000, 1500, or 2000 gpm (2900, 3800, 5700, or 7600 lpm)
- Pick up rates: 750, 1000, 1500, 2000 gpm at 1% and 3%; 750, 1000 gpm (2900, 3800 lpm) at 6%
- Manual pattern control
- Pick up hose available in 10' (3 m) with a 40" (102 cm) tube
- Swivel inlet: 3.5" (89 mm)
- Length: 13.75" (322 mm)
- Weight: 17.4 lbs. (7.89 kg)

LIST PRICE (US Dollars, FOB Wooster, OH USA)

Prices below supersedes any pricing that was published prior to June 27, 2013

Akrofoam 2000 Master Stream Nozzle only.....	\$2,328.00
Akrofoam 2000 Master Stream Nozzle with Pickup Hose/Tube.....	\$2,620.00
Akrofoam 2000 Master Stream Nozzle with Pickup Hose/Tube and Foam Shutoff Valve.....	\$2,762.00
Akrofoam 2000 Master Stream Nozzle with Pickup Hose/Tube and Foam Metering Valve.....	\$3,379.00

AVAILABILITY

Currently Available

News Bulletin

New Product Release



SPECIFICATION

A Combination fog and straight stream constant gallonage nozzle with four flow settings – 750, 1000, 1500, and 2000 gpm (2900, 3800, 5700, and 7600 lpm) shall be provided. Flow settings shall be capable of being changed by the rotation of the spring loaded baffle head. The nozzle shall have a 3.5" (89 mm) swivel inlet, storage of the foam orifice plates located on the nozzle. The nozzle shall have the option of a 10' (3 m) CAM lock quick disconnect foam pick up hose, a CAM lock cap for the foam pick up port, and a foam metering valve with foam shutoff. The nozzle shall be constructed of durable, lightweight Pyrolite with a weight less than 17.5 lbs. (7.94 kg) and a maximum length of 13.75" (322 mm).