

Omega SD Monitor 4" flange x 2.5" NH outlet, monitor only

STYLE 3524

The Omega SD Severe Duty brass monitors utilize a unique ball bearing free joint design ideal for high usage applications.

Features

Omega SD Severe-Duty Monitor

- Ideal for high usage applications - Mining - Tank Cleaning - Equipment Wash Down
- New longer tiller bar that can be mounted in 30 degree increments for increased control
- Extensive duty-cycle use
- Brass & stainless steel construction
- Cast in turning vanes
- Unique severe-duty joint design - Maximum Flow: 1250 gpm (4800 lpm) - Maximum Pressure: 200 psi (14 bar)

- Articulation: 360° Horizontal -90° to +90° Vertical - Friction Loss 12 psi @ 1000 gpm

Applications/Solutions

- Mining



Specifications

Style	3524
Weight	58.5 lbs (26.5 kg)
Type	Industrial
Material	Brass
Brand	Omega
Width	14 3/16" (360 mm)
Height	13 15/16" less nozzle (354 mm)
Depth	26 5/8" (676 mm)
Inlet	3" standard 4" optional (75 mm standard 100 mm optional)
Outlet	2.5" NH (65 mm)
Flow (GPM)	1250
Flow (LPM)	4800