

# **Self-Educting**

Self-Educting master stream nozzles turn any monitor into a foam station without the use of additional equipment and have been part of Elkhart's fire suppression arsenal for over 20 years. Elkhart is proud to have been one of the pioneers in the development of the Hydro-Foam® line of self-educting nozzles.

Some of the features of self-educting nozzles include:

- Designed specifically for use with Class A and B foam, including AFFF and fluoroprotein
- Field-adjustable foam proportioning with pre-set options
- Combination nozzle include straight stream, narrow fog (30°), or wide fog (90°)

Since introduction, Elkhart has expanded the self-educting Master Stream nozzle line to include:

- Easy to use, original Hydro-Foam® nozzles of brass or Elk-O-Lite® construction
- X-Stream® nozzles that combine self-educting ability with the convenience of automatic metering



### **SELF-EDUCTING**

	NOZZLE FAMILY									
	X-Stream <sup>®</sup>	Hydro-Foam®								
Flow Type	Automatic	Fixed								
Description	High flow automatic nozzle	Original self-educting nozzle								
Benefit	Optimizes use of concentrate and produces effective foam under a variety of conditions	Simple to use and flows well. Elk-O-Lite® version is lightweight and excellent for portable monitor use.								
Foam Proportioning	Dual range, field selectable (SM-1000-HF and SM-1000E-HF) or fixed metering (SM-2000-HF and SM-2000E-HF)	Fixed metering via orifice insert								

# **OPTIONS**

- SM-1000E-HF features an 8' pick-up tube
- SM-2000E-HF features an 8' pick-up tube

#### **THREADS**

All nozzles are NHT unless otherwise specified. See index T-13 for optional base threads.

	FAMILY / FLOW RATE						FOAM PROPORTIONING						Certifications	MATERIAL / FINISH								
Base Size	X-STREAM®/ HYDRO- AUTOMATIC FOAM®/FIXED					CONFIGURABLE				SELECTABLE			Certific	BRASS								
	GPM (LPM)																					
		750- 2000 (2839- 7571)	350 (1325)	500 (1893)	750 (2839)	1000 (3785)	₩7%	1%	3%		1% / 3%		ric	UL Listed	s (Satin)	me	Composite	Elk-O-Lite®	Effective Reach (Ft.)	jht (Lbs.)	)FL	RE
		PSI (BAR) 100 (6.89)											Electric	UL Li	Brass	Chrome	Com	EK-C	Effec	Weight	MODEL	FIGURE
			•				•	•	•	•				•	S	0			145	13.2	HF-350	1
			•				•	•	•	•								S	145	4.2	HF-350-A	1
				•			•	•	•					•	S	0			162	13.2	HF-500	1
2″				•			•	•	•									S	162	4.2	HF-500-A	1
2.5	•			_					_			S						S	250	20.7	SM-1000-HF	2
. •	•			<u> </u>			_			_		S	•					S	250	20.7	SM-1000E-HF	3
	Selectable: 500 / 750 / 1000								•	_		_			S				212	22	CSW-LBF	4
					•		_			_		S			S					22	HF13-750 HF13-1000	5
*		•				•	_	•		_		S			S			S	295	21.6	SM-2000-HF	2
.5.		•						•					•					5	295	21.6	SM-2000-HF	3
KEY																						

# **SELF-EDUCTING FOAM CONFIGURATIONS**



Figures depict general product types only and are not intended to be inclusive of all product features.

<sup>\*</sup>Fog pattern is 80°

### SELF-EDUCTING NOZZLE ACCESSORIES



#### **QUICK-CONNECT COUPLING**

- · The brass Quick-Connect Coupling is a convenient way of attaching/detaching pick-up hose
- Specify brass or chrome finish
- Length: 3.4"
- · Weight: 1.2 lbs.

#### **SHUT-OFF VALVE**

- · Quarter turn ball valve for positive shut-off of foam supply
- · Attaches to foam inlet of nozzle
- · Specify chrome or brass finish



#### **METERING VALVE**

- · The quarter turn ball valve for instant proportioning change
- Available in 1% / 3% or 3% / 6% configurations
- Attached to foam inlet of nozzle
- · Specify chrome or brass finish
- · Length: 3"
- · Weight: 1.3 lbs.



#### **DRUM PICK-UP KIT**

- Allows foam inlet of nozzle to be pre-connected to a 55 gallon drum of concentrate
- Kit 1 includes PVC pick-up tube with shut-off valve, brass vacuum breaker, and clear reinforced vinyl pick-up hose (8 feet)
- Kit 3 or Kit 4 includes PVC pick-up tube with shut-off valve only. Replaces non-valve pick-up tube that comes with nozzle.


COMPATIBLE ACCESSORIES									
	FOAM NOZZLE								
ITEM	X-Str	Hydro-Foam®							
	SM-1000 HF	SM-2000 HF	350/A	500/A					
Quick-connect			•	•					
Shut-off Value with Quick-connect			•	•					
1% / 3% Metering Valve with Quick-connect			•	•					
3% / 6% Metering Valve with Quick-connect			•						
Shut-off Valve			•	•					
1% / 3% Metering Valve			•	•					
3% / 6% Metering Valve			•						
Drum Pick-up Kit 1			•	•					
Drum Pick-up Kit 3	•								
Drum Pick-up Kit 4		•							

(STD)

Hose Clamp

**SELF-EDUCTING NOZZLE ACCESSORIES** 

# OPTIONAL HARDWARE FOR FOAM INLET LINE



**NOTE:** These illustrations show typical combinations of valves and fittings. Other combinations can be provided to satisfy customer needs.

ELKHARI

Female Quick Connect (OPT)